

ProMAXX-Pipe Cutter*

Reliable Severing of Single or Multiple Casing Strings

APPLICATIONS

- Well abandonment
- Single trip cut and pull operations
- Slot Recovery
- Carbon Capture Utilization and Storage (CCUS) operations
- Internal cutting of single or multiple strings of casing

BENEFITS

- Ball drop activation and Flow Through-bore
- Enhanced operational efficiency, reducing overall project timelines
- Substantial cost savings by eliminating the need for multiple interventions
- Through-bore allows flow to facilitate cementing, setting of a hydraulic bridge plug, and cement plug dressing operations, prior to activation

FEATURES

- Rapid and precise casing-cutting technology using TruEdge* cutting structure
- Hydraulically actuated cutter arms ensure cutter opening
- Unique annular flotel design providing a clear pressure indication of cut completion
- Designed to cut a range of casing size of 9⁵/₈ inch and 13³/₈ inch
- Built in full gauge stabilizer to improve the cutting efficiency

Through-bore access and a ball-drop activation mechanism

The ProMAXX-Pipe Cutter is designed to cut both single and multiple strings of pipe. It operates hydraulically, using a ball drop and pump pressure to actuate the knife arms, and is designed to allow full flow through the bore of the tool to the string below.

The flow-through feature enables other operations, such as cementing, cement plug dressing, or bridge plug setting, before activating the pipe cutter.

The knives of the ProMAXX-Pipe Cutter are assembled with WIS propriety TruEdge insert-only knives, and multiple cuts can be made in the same trip without needing a trip to recover to the surface.

The ProMAXX-Pipe Cutter chassis is mounted with a full-gauge stabilizer, which helps improve cutting efficiency by providing stabilization very close to the cutter knives.

CO₂ Emission Reduction by saving rig time

When combined with the ProMAXX-Hydraulic Spear, the system provides a one-trip solution for cutting, anchoring, and retrieving the casing without pulling to the surface to change tools.

By combining multiple operations in a single trip, rig time and cost is reduced significantly. Operational time savings also result in considerable emissions reduction.

PROMAXX-PIPE CUTTER SPECIFICATIONS

Pipe Cutter Size, in.	8.25
Casing Size Range, in.	9 ⁵ / ₈ – 13 ³ / ₈
Top Connection, in.	NC50 Box
Fishing Neck OD, in.	6.5
Weight, lb	900



ProMAXX-Pipe Cutter

*Mark of Wellbore Integrity Solutions. Other company, product, and service names are the properties of their respective owners.
Copyright © 2023 Wellbore Integrity Solutions.
All rights reserved. WIS-FS-MKT-189_rev3